

DESIGN REQUIREMENTS MANUAL

CI-0401

TAB 4: STATION INFRASTRUCTURE

Station Buildings

PUBLIC WASHROOMS	
Room Name	Description
Location	> In station attendant line of sight.
Features	Public Washrooms shall be determined as universal or multi-use in addition to universal washrooms based on patronage and size of the station building.
	> A minimum of one universal washroom shall be provided.
	Universal washrooms shall be provided with provisions for the future installation of an adult change table. An emergency two-way call system shall be provided in universal washrooms and shall follow the same call flow as the two-way intercoms as outside elevators (ie. to Station Attendant first, then Transit Safety, etc.)
	A minimum of one barrier-free water closet stall shall be provided in a multi-use washroom.
	In universal washrooms, door swing and/or screens shall at least partially obstruct the line of vision to water closets and urinals.
	Signage shall be provided that advises patrons to lock the door behind them for privacy.
	> All plumbing fixtures to be located on interior walls.
Doors	> Entrance to multi use washrooms shall be door less.
	In multi-use washrooms, doors shall have closers, and be undercut for exhaust make-up air (doors shall not have louvers).
	Single use Door hardware to be a lever handle passage set, and a latch, operable from the interior, to display "vacant" or "occupied".
	> Barrier-free power door operators shall be provided for universal washrooms.