



ASSEMBLY OF 16'-6" POINT RAIL

RIGHT HAND POINT RAIL - GTS 313 A

LEFT HAND POINT RAIL - GTS 313 B (ILLUSTRATED)

POINT ASSEMBLY INCLUDES:

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY	
			DWG. No. GTS-0313	
			A	B
1	RIGHT POINT RAIL LEFT POINT RAIL	R11C-556.1 R11C-556.1	1 -	- 1
2	STOCK SIDE REINFORCING BAR 1/2" THK. x 14'-3" LG.	GTS-0342/G	1	1
3	GAUGE SIDE REINFORCING BAR 1-1/4" THK. x 14'-3" LG.	GTS-0342/P	1	1
4	STOP BLOCK	GTS-0339/J	1	1
5	3/4" DIA-10 UNC SQ. HD. BOLT x 4-3/4" LG. C/W SQ. NUT	GTS-1305/9	2	2
6	1" DIA-8 UNC SQ. HD. BOLT x 4-1/4" LG. C/W SQ. NUT	GTS-1309/24	12	12
7	SPRING WASHER FOR 3/4" DIA. BOLT	GTS-1301	2	2
8	SPRING WASHER FOR 1" DIA. BOLT	GTS-1301	12	12
9	3/16" COTTER PIN x 1-1/4" LONG		2	2

NOTE: THE FOLLOWING ITEMS ARE NOT INCLUDED IN THE SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY	
			DWG. No. GTS-0313	
			A	B
10	MJS CLIP ASSEMBLY (352E)	GTS-0352/E	1	1
11	MJS CLIP ASSEMBLY (352F)	GTS-0352/F	2	2

NOTES:

-SWITCH CLIPS ARE NOT INCLUDED IN SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.

-WHEN REFERRING TO POINT RAILS, DRAWING No. MUST BE STATED AS A OR B TO INDICATE RIGHT OR LEFT HAND POINT:

A - RIGHT HAND POINT
B - LEFT HAND POINT (ILLUSTRATED)

METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm

1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	
No.	Date	Revision	By Approved

Standard / **ASSEMBLY**
16'6" POINT RAIL
FOR SPRING OPERATION-115LB. R.E. RAIL

Drawn GGS Checked GWM Approved *[Signature]*
VP Engineering & Asset Management



Date SEPT 15/2017 Plan Number GTS-0313 Rev 1

REFERENCE: TS-0313_R2 Sheet 1 OF 1