



ASSEMBLY OF 16'-6" POINT RAIL
 RIGHT HAND POINT RAIL - GTS 317 A
 LEFT HAND POINT RAIL - GTS 317 B (ILLUSTRATED)

POINT ASSEMBLY INCLUDES:

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY DWG. No. GTS-0317	
			A	B
1	RIGHT POINT RAIL LEFT POINT RAIL	R11C-602.1 R11C-602.1	1 -	- 1
2	REINFORCING BAR 1/2" THK. X 15'-0" LONG	GTS-0342/J	2	2
3	STOP BLOCK	GTS-0339/M	1	1
4	3/4" DIA-10 UNC SQ. HD. BOLT x 4" LG. C/W SQ. NUT	GTS-1305/6	2	2
5	1" DIA-8 UNC SQ. HD. BOLT x 3-1/2" LG. C/W SQ. NUT	GTS-1309/13	14	14
6	SPRING WASHER FOR 3/4" DIA. BOLT	GTS-1301	2	2
7	SPRING WASHER FOR 1" DIA. BOLT	GTS-1301	14	14
8	3/16" COTTER PIN X 1-1/4" LONG		2	2

NOTE: THE FOLLOWING ITEMS ARE NOT INCLUDED IN THE SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY DWG. No. GTS-0317	
			A	B
9/10	<u>SIDE JAW CLIPS</u> SWITCH CLIP - RIGHT HAND (338 A-3) SWITCH CLIP - LEFT HAND (338 B-3)	GTS-0338/5 GTS-0338/6	2 -	- 2
9	<u>MJS CLIPS</u> MJS CLIP ASSEMBLY (352G)	GTS-0352/G	1	1
10	MJS CLIP ASSEMBLY (352H)	GTS-0352/H	1	1

NOTES:

- SWITCH CLIPS ARE NOT INCLUDED IN SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.
- WHEN REFERRING TO POINT RAILS, DRAWING No. MUST BE STATED AS A OR B TO INDICATE RIGHT OR LEFT HAND POINT:
 A - RIGHT HAND POINT
 B - LEFT HAND POINT (ILLUSTRATED)

METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm

No.	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	By Approved
Standard		ASSEMBLY 16'6" POINT RAIL FOR POWER OPERATION 132LB. R.E. RAIL GRADUATED RISER	
Drawn	GGS	Checked	GWM
		Approved	<i>[Signature]</i> VP Engineering & Asset Management
Date	SEPT 15/2017	Plan Number	GTS-0317
REFERENCE: TS-0317_R1		Rev 1	
		Sheet 1 OF 1	