



### ASSEMBLY OF 22'-0" POINT RAIL

RIGHT HAND POINT RAIL - GTS 329 A  
 LEFT HAND POINT RAIL - GTS 329 B (ILLUSTRATED)

POINT ASSEMBLY INCLUDES:

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY	
			DWG. No. GTS-0329 A	B
1	RIGHT POINT RAIL LEFT POINT RAIL	R11C-562.1 R11C-562.1	1 -	- 1
2	STOCK SIDE REINFORCING BAR 1/2" THK. x 19'-0" LG.	GTS-0342/H	1	1
3	GAUGE SIDE REINFORCING BAR 1-1/4" THK. x 19'-0" LG.	GTS-0342/R	1	1
4	STOP BLOCK No. 1	GTS-0339/K	1	1
5	STOP BLOCK No. 2	GTS-0339/L	1	1
6	3/4" DIA-10 UNC SQ. HD. BOLT x 4-3/4" LG. C/W SQ. NUT	GTS-1305/9	4	4
7	1" DIA-8 UNC SQ. HD. BOLT x 4-1/4" LG. C/W SQ. NUT	GTS-1309/24	16	16
8	SPRING WASHER FOR 3/4" DIA. BOLT	GTS-1301	4	4
9	SPRING WASHER FOR 1" DIA. BOLT	GTS-1301	16	16
10	3/16" COTTER PIN x 1-1/4" LONG		4	4

NOTE: THE FOLLOWING ITEMS ARE NOT INCLUDED IN THE SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.

ITEM NO.	DESCRIPTION	STANDARD PLAN NO.	QUANTITY	
			DWG. No. GTS-0329 A	B
11	MJS CLIPS MJS CLIP ASSEMBLY (352E)	GTS-0352/E	1	1
12	MJS CLIP ASSEMBLY (352F)	GTS-0352/F	3	3

### NOTES:

-SWITCH CLIPS ARE NOT INCLUDED IN SWITCH POINT ASSEMBLY AND MUST BE ORDERED SEPARATELY IF REQUIRED.

-WHEN REFERRING TO POINT RAILS, DRAWING No. MUST BE STATED AS A OR B TO INDICATE RIGHT OR LEFT HAND POINT:

- A - RIGHT HAND POINT
- B - LEFT HAND POINT (ILLUSTRATED)

**METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm**

1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	
No.	Date	Revision	By Approved
Standard		<b>ASSEMBLY 22'0" POINT RAIL FOR SPRING OPERATION 115 LB. R.E. RAIL</b>	
Drawn	GGS	Checked	GWM
		Approved	<i>[Signature]</i> VP Engineering & Asset Management
Date	SEPT 15/2017	Plan Number	GTS-0329
		Rev	1
REFERENCE: TS-0329_R2		Sheet 1 OF 1	