



RIGHT & LEFT HAND

NOTES:

- 1/2" MIN. IDENTIFICATION CHARACTERS RAISED 1/32" TO BE CAST ON EACH BLOCK, AS SHOWN.
- DIMENSIONS ARE FOR FINISHED BLOCKS. PROPER ALLOWANCES MUST BE MADE FOR SHRINKAGE WHEN MAKING PATTERNS.
- ALL BEARINGS SURFACES SHALL BE FINISHED TO GIVE AN ACCURATE FIT AGAINST RAIL.

MATERIAL:

HEEL BLOCKS SHALL BE OF CAST STEEL IN ACCORDANCE WITH GO SPECIFICATION 12-9, APRIL 1983.  
PAGE 12 SECTION 8.2.4 AND A.S.T.M STANDARD A148. GRADE 80-40

METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm

No.	Date	Revision	By
1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	

Standard / **HEEL BLOCKS FOR 16'-6" & 22'-0" SWITCHES 132LB. R.E. RAIL**

Drawn MG Checked GGS Approved *[Signature]* VP Engineering & Asset Management



Date DEC 15, 2017 Plan Number GTS-0360 Rev 1

REFERENCE: TS-360 Sheet 1 OF 1