



- NOTES:**
- 1- POINT MACHINING DETAILS ON THIS DRAWING ARE FOR RIGHT HAND TURNOUTS ONLY, POINTS FOR LEFT HAND TURNOUTS ARE MACHINED TO OPPOSITE HAND.
 - 2- THIS IS A MACHINING DRAWING FOR SAMSON POINT RAILS-FOR ASSEMBLY SEE GTS-378 A/D 36'-7" SAMSON POINT RAIL FOR POWER OPERATION.
 - 3- ALL HOLES ARE TO BE DRILLED: THE USE OF ACETYLENE TORCH OR OTHER BURNING METHOD FOR THE MAKING OF HOLES OR CUTTING IN THE MANUFACTURE OF POINTS IS ABSOLUTELY PROHIBITED.

MATERIAL:
 RAIL: UNLESS SPECIFIED OTHERWISE POINT RAILS SHALL BE ALLOY RAIL IN ACCORDANCE WITH SPECIFICATION 12.4 LATEST ISSUE.
 REINFORCING BARS: SEE GTS-342

METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm			
No.	Date	Revision	By Approved
1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	
Standard		MACHINING DETAILS-UNIFORM RISER DESIGN 58'-10" SAMSON POINT RAIL NO. 20 LATERAL ALL WELDED TURNOUT FOR POWER OPERATED-136LB. R.E. RAIL	
Drawn	Checked	Approved	
MG	GGG	VP Engineering & Asset Management	
Date	Plan Number	GTS-0441	Rev 1
REFERENCE: TS-441			Sheet 1 OF 1