



TYPICAL PANDROL SHOULDER INSTALLATION

**NOTES**

1. WHEN REFERRING TO SWITCH PLATES, PLAN AND PLATE NUMBERS MUST BE STATED TO INDICATE SPECIFIC PLATE REQUIRED.
2. IDENTIFICATION CHARACTERS ( 1/2 "MINIMUM HEIGHT) TO BE STAMPED ON EACH PLATE AS SHOWN.
3. ALL DIMENSIONS ARE IN INCHES.
4. UNLESS OTHERWISE SPECIFIED ALL TOLERANCES TO BE ±1/32.

**MATERIAL**

PLATES TO CONFORM TO THE LATEST REVISION OF GO TRANSIT TRACK STANDARDS OR IN GENERAL WITH LATEST REVISION OF A.S.T.M. SPECIFICATION FOR COMMERCIAL QUALITY HOT ROLLED BAR STEEL A-675 CHEMICAL REQUIREMENT.

	MINIMUM	MAXIMUM
CARBON	0.15 %	0.25 %
MANGANESE	0.30 %	0.60 %
PHOSPHORUS		0.04 %
SULPHUR		0.05 %

PLATES	A	B	C	D	E	STOCK NUMBERS	
	±1/8	±1/16		+1/32 -0		NEW	PART WORN
SP-380	18-1/4	16-7/8	12-13/32	6-3/32	0		
SP-381	18-3/4	17-3/8	12-27/32	6-17/32	13/64		

**METRIC CONVERSION: 1 inch=25.4mm, 1 foot=304.8mm**

1	18/07/27	ADDED IMPERIAL TO METRIC CONVERSION NOTE	
No.	Date	Revision	By Approved

Standard / **SWITCH PLATES**

Drawn MG Checked GGS Approved *[Signature]*  
VP Engineering & Asset Management



**METROLINX**

Date DEC 15, 2017 Plan Number GTS-0609 Rev 1

REFERENCE: TS-609 Sheet 1 OF 1