



NOTES

1. WHEN REFERRING TO SWITCH PLATES, PLAN AND PLATE NUMBERS MUST BE STATED TO INDICATE SPECIFIC PLATE REQUIRED.
2. IDENTIFICATION CHARACTERS (1/2 "MINIMUM HEIGHT) TO BE STAMPED ON EACH PLATE AS SHOWN.
3. ALL DIMENSIONS ARE IN INCHES.
4. UNLESS OTHERWISE SPECIFIED ALL TOLERANCES TO BE ± 1/32.

MATERIAL

PLATES TO CONFORM TO THE LATEST REVISION OF GO TRANSIT TRACK STANDARDS OR IN GENERAL WITH LATEST REVISION OF A.S.T.M. SPECIFICATION FOR COMMERCIAL QUALITY HOT ROLLED BAR STEEL A-675 CHEMICAL REQUIREMENT.

	MINIMUM	MAXIMUM
CARBON	0.15 %	0.25 %
MANGANESE	0.30 %	0.60 %
PHOSPHORUS	0.04 %	0.04 %
SULPHUR		0.05 %

PLATES	A	B	C	D	E	F	G	WEIGHT (LBS.)	STOCK NUMBERS	
	±1/8	±1/16							NEW	PART WORN
SP-665	28-3/4	27-3/8	22-35/64	16-11/64	1°	3-33/64	3-41/64			
SP-666	29-1/4	27-7/8	23-1/32	16-21/32	1°	4	4-9/64			
SP-667	29-3/4	28-3/8	23-17/32	17-5/32	1°	4-31/64	4-5/8			

0	17/12/15	REVISED PDF VERSION ESTABLISHED
No.	Date	Revision
		By Approved

Standard / **FOR EQUILATERAL TURNOUT SWITCH PLATES**

Drawn MG Checked RP Approved *MBL*
VP Corridor Infrastructure



METROLINX

Date DEC 15, 2017 Plan Number GTS-0641 Rev 0

REFERENCE: TS-641

Sheet 1 OF 1