

IDENTIFICATION CHARACTERS, 1/2 MIN HEIGHT, STAMPED CLEARLY ON EACH ANGLE



2 SLOTS, 13/16 X 1-13/16

NOTES:

1. CONVERSION FACTOR: 1 INCH=25.4mm, 1 FOOT=304.8mm.
2. ALL DIMENSIONS ARE IN INCHES.
3. BOLT HOLES SHALL BE PUNCHED.
4. THE USE OF ACETYLENE TORCH OR OTHER BURNING METHOD , FOR THE CUTTING OR MAKING OF HOLES IN THE MANUFACTURE OF LOCKING ANGLES, IS ABSOLUTELY PROHIBITED.

MATERIAL:

- LOCKING ANGLE TO CONFORM IN GENERAL WITH LATEST REVISION OF A.S.T.M. SPECIFICATION FOR GENERAL REQUIREMENTS FOR HOT ROLLED AND COLD FINISHED CARBON AND ALLOY STEEL BARS, A29.
- LOCKING ANGLE FROM 3/16 X 1-3/4 X 1-1/4 STANDARD ANGLE.

| | | | |
|---|-------------|---|---|
| 0 | 17/12/15 | DWG VERSION ESTABLISHED | |
| No. | Date | Revision | By Approved |
| Standard/ | | MOUNTING BOLT LOCKING ANGLE FOR SWITCH STANDS | |
| Drawn | LG | Checked | DGRL |
| | | Approved | <i>KBL/LL</i> VP Corridor Infrastructure |
|  | |  | |
| Date | DEC 15/2017 | Plan Number | GTS-0708 |
| | | Rev | 0 |
| REFERENCE: TS-708 | | | Sheet 1 OF 1 |