


SECTION B-B

GTS-1107B REQUIRE ONE 12' & ONE 39' 85LB. RAIL MANUFACTURED AS INDICATED BELOW D REQUIRE ONE 12' & ONE 39' 100LB. RAIL MANUFACTURED AS INDICATED BELOW F REQUIRE ONE 12' & ONE 39' 115LB. RAIL MANUFACTURED AS INDICATED BELOW H REQUIRE ONE 12' & ONE 39' 132LB. RAIL MANUFACTURED AS INDICATED BELOW



DRAWING	WEIGHT OF	A+1/32	B+1/32	C+1/32	D+1/64 -0	E+1/16	F+1/16	G+1/8	H+1/16	J+1/64 -0
NUMBER GTS-1107A	RAIL 85 LB.	2-7/16	8-15/16	'	1-3/16	2-11/32	3-1/4	1' 10-3/8"	2-11/32	1-1/16
GTS-1107B	85 LB.	2-7/16	8-15/16		1-3/16	2-11/32	3-1/4	1' 10-3/8"	2-11/32	1-1/16
GTS-1107C	100 LB.	2-11/16	8-3/16	13-11/16	1-7/16	2-3/4	3-1/2	2' 1-5/8"	2-3/4	1-3/16
<b>G</b> TS-1107D	100 LB.	2-11/16	8-3/16	13-11/16	1-7/16	2-3/4	3-1/2	2' 1-5/8"	2-3/4	1-3/16
GTS-1107E	115 LB.	3-1/2	9-1/2	15-1/2	1-9/16	3-1/32	3-1/2	2' 1-5/8"	2-7/8	1-3/16
GTS-1107F	115 LB.	3-1/2	9-1/2	15-1/2	1-9/16	3-1/32	3-1/2	2' 1-5/8"	2-7/8	1-3/16
GTS-1107G	132 LB.	3-1/2	9-1/2	15-1/2	1-9/16	3-3/32	3-3/4	2' 4-3/4"	3-3/32	1-5/16
CTC 1107⊔	12210	2 1/2	0.1/2	15 1/2	1 0/16	2 2/22	2 2/1	2 / 1 2 / 1	2 2/22	1 5/16

## NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES, UNLESS OTHERWISE SPECIFIED.
- 2. THE USE OF ACETYLENE TORCH OR OTHER BURNING METHOD FOR THE CUTTING OR MAKING OF HOLES IN THE RAIL IS ABSOLUTELY PROHIBITED.
- 3. ALL HOLES MUST BE DRILLED BEFORE RAILS ARE BENT.
- 4. A 52' BENT TYPE GUARD RAIL, MADE UP OF ONE 39' RAIL AND ONE 12' RAIL, MAY BE ORDERED BY STATING DRAWING NUMBER AND LEFT OR RIGHT HAND, I.E. GTS-1107A (RIGHT HAND)

